SN-IRC13/62ASDN HDVI Camera

Datasheet

Model	SN-IRC13/62ASDN
Image Sensor	Sony 1/3 "1.3Mega Progressive Scan CMOS
Effective Pixels	1280 (H) × 960 (V)
Signal system	720p @ 50fps / 720p @ 60fps
Video frame rate	PAL: 1/50 ~ 1/100000 sec NTSC: 1/60 ~ 1/100000 sec
Horizontal Resolution	900TVL
Mini. Illumination	0.001Lux @ (F1.2, AGC ON), 0 Lux with IR 0.0005Lux @ (F1.4, AGC ON), 0 Lux with IR
Video Output	1 CH HDVI HD output
Max. IR LEDs Length	20m
IR LEDs	φ5X30PCS
Lens	Fixed focus 3.6mm (6mm optional)
Noise Reduction	3D (Low, Middle, High,OFF)
BLC	Auto
Gain	Auto
WDR	D-WDR
Day/Night	Auto(ICR)
SNR	>50db
Maximum transmission distance	75-5 coaxial cable transmission over 300 m
Sync mode	Internal
Transmission Distance	Over 500m via 75-5 coaxial cable
Power Supply	DC12V±10%
Ingress Protection	IP66
Power Consumption	Max 5W
Working Environment	-10 °C ~ + 55 °C, humidity less than 85% (non-condensing)
Installation	Wall mounted, ceiling mounted
Weight	650g

Specifications/Features:

◆ Using SONY high performance CMOS image sensors,perfectly capturing a moving object;
◆ Auto switch movable ICR
◆Support Coaxial HD output, clear and exquisite images, resolution up to 720p @ 50fps / 720p @ 60fps;
◆Use the matrix spot lens to match the sensor area, substantial increase energy utilization;
◆Universal adjustable structure, convenient adjustment, high reliability;
◆IR Distance 25M
◆Adopting 30PCs ϕ5mm IR Leds
◆Metal anti-smashing, with IP66 waterproof design;

Sunell HQ is located in Shenzhen close to the international airport of Hong Kong.

Phone: +86 755 8602 6374
Skype: sunellinfo
Email: sales@sunellsecurity.com
Address: Floors 1-5
Aerospace Micromotor Buildings, Lanshan 2nd Road,
Hi-Tech Industrial Park (North),
Nanshan, Shenzhen 518057

Join our mailing list for updates & news.